

ZyXEL M-202

XtremeMIMO 802.11g Wireless USB Adapter

User's Guide

Version 1.0
1/2006

The logo for ZyXEL, featuring the word "ZyXEL" in a bold, blue, sans-serif font. The "Zy" is in a slightly larger font size than "XEL".

Copyright

Copyright © 2006 by ZyXEL Communications Corporation.

The contents of this publication may not be reproduced in any part or as a whole, transcribed, stored in a retrieval system, translated into any language, or transmitted in any form or by any means, electronic, mechanical, magnetic, optical, chemical, photocopying, manual, or otherwise, without the prior written permission of ZyXEL Communications Corporation.

Published by ZyXEL Communications Corporation. All rights reserved.

Disclaimer

ZyXEL does not assume any liability arising out of the application or use of any products, or software described herein. Neither does it convey any license under its patent rights nor the patent rights of others. ZyXEL further reserves the right to make changes in any products described herein without notice. This publication is subject to change without notice.

Trademarks

ZyNOS (ZyXEL Network Operating System) is a registered trademark of ZyXEL Communications, Inc. Other trademarks mentioned in this publication are used for identification purposes only and may be properties of their respective owners.

Federal Communications Commission (FCC) Interference Statement

The device complies with Part 15 of FCC rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operations.

This equipment has been tested and found to comply with the limits for a Class B digital device pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

If this equipment does cause harmful interference to radio/television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- 1 Reorient or relocate the receiving antenna.
- 2 Increase the separation between the equipment and the receiver.
- 3 Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- 4 Consult the dealer or an experienced radio/TV technician for help.

Notice 1

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.


This product has been designed for the WLAN 2.4 GHz network throughout the EC region and Switzerland, with restrictions in France.

Caution

- 1 The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment, under 47 CFR 2.1093 paragraph (d)(2).
- 2 This Transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

Certifications

- 1 Go to www.zyxel.com.
- 2 Select your product from the drop-down list box on the ZyXEL home page to go to that product's page.
- 3 Select the certification you wish to view from this page.



注意！

依據 低功率電波輻射性電機管理辦法

第十二條 經型式認證合格之低功率射頻電機，非經許可，公司、商號或使用者均不得擅自變更頻率、加大功率或變更原設計之特性及功能。

第十四條 低功率射頻電機之使用不得影響飛航安全及干擾合法通信；經發現有干擾現象時，應立即停用，並改善至無干擾時方得繼續使用。
前項合法通信，指依電信規定作業之無線電信。低功率射頻電機須忍受合法通信或工業、科學及醫療用電波輻射性電機設備之干擾。

ZyXEL Limited Warranty

ZyXEL warrants to the original end user (purchaser) that this product is free from any defects in materials or workmanship for a period of up to two (2) years from the date of purchase. During the warranty period, and upon proof of purchase, should the product have indications of failure due to faulty workmanship and/or materials, ZyXEL will, at its discretion, repair or replace the defective products or components without charge for either parts or labor, and to whatever extent it shall deem necessary to restore the product or components to proper operating condition. Any replacement will consist of a new or re-manufactured functionally equivalent product of equal or higher value, and will be solely at the discretion of ZyXEL. This warranty shall not apply if the product has been modified, misused, tampered with, damaged by an act of God, or subjected to abnormal working conditions.

Note

Repair or replacement, as provided under this warranty, is the exclusive remedy of the purchaser. This warranty is in lieu of all other warranties, express or implied, including any implied warranty of merchantability or fitness for a particular use or purpose. ZyXEL shall in no event be held liable for indirect or consequential damages of any kind to the purchaser.

To obtain the services of this warranty, contact ZyXEL's Service Center for your Return Material Authorization number (RMA). Products must be returned Postage Prepaid. It is recommended that the unit be insured when shipped. Any returned products without proof of purchase or those with an out-dated warranty will be repaired or replaced (at the discretion of ZyXEL) and the customer will be billed for parts and labor. All repaired or replaced products will be shipped by ZyXEL to the corresponding return address, Postage Paid. This warranty gives you specific legal rights, and you may also have other rights that vary from country to country.

Online Registration

Register your product online to receive e-mail notices of firmware upgrades and information at www.zyxel.com for global products, or at www.us.zyxel.com for North American products.

Customer Support

Please have the following information ready when you contact customer support.

- Product model and serial number.
- Warranty Information.
- Date that you received your device.
- Brief description of the problem and the steps you took to solve it.

METHOD	SUPPORT E-MAIL	TELEPHONE ^A	WEB SITE	REGULAR MAIL
LOCATION	SALES E-MAIL	FAX	FTP SITE	
CORPORATE HEADQUARTERS (WORLDWIDE)	support@zyxel.com.tw	+886-3-578-3942	www.zyxel.com www.europe.zyxel.com	ZyXEL Communications Corp. 6 Innovation Road II Science Park Hsinchu 300 Taiwan
	sales@zyxel.com.tw	+886-3-578-2439	ftp.zyxel.com ftp.europe.zyxel.com	
CZECH REPUBLIC	info@cz.zyxel.com	+420-241-091-350	www.zyxel.cz	ZyXEL Communications Czech s.r.o. Modranská 621 143 01 Praha 4 - Modrany Ceská Republika
	info@cz.zyxel.com	+420-241-091-359		
DENMARK	support@zyxel.dk	+45-39-55-07-00	www.zyxel.dk	ZyXEL Communications A/S Columbusvej 2860 Soeborg Denmark
	sales@zyxel.dk	+45-39-55-07-07		
FINLAND	support@zyxel.fi	+358-9-4780-8411	www.zyxel.fi	ZyXEL Communications Oy Malminkaari 10 00700 Helsinki Finland
	sales@zyxel.fi	+358-9-4780 8448		
FRANCE	info@zyxel.fr	+33-4-72-52-97-97	www.zyxel.fr	ZyXEL France 1 rue des Vergers Bat. 1 / C 69760 Limonest France
		+33-4-72-52-19-20		
GERMANY	support@zyxel.de	+49-2405-6909-0	www.zyxel.de	ZyXEL Deutschland GmbH. Adenauerstr. 20/A2 D-52146 Wuerselen Germany
	sales@zyxel.de	+49-2405-6909-99		
HUNGARY	support@zyxel.hu	+36-1-3361649	www.zyxel.hu	ZyXEL Hungary 48, Zoldlomb Str. H-1025, Budapest Hungary
	info@zyxel.hu	+36-1-3259100		
KAZAKHSTAN	http://zyxel.kz/support	+7-3272-590-698	www.zyxel.kz	ZyXEL Kazakhstan 43, Dostyk ave., Office 414 Dostyk Business Centre 050010, Almaty Republic of Kazakhstan
	sales@zyxel.kz	+7-3272-590-689		
NORTH AMERICA	support@zyxel.com	1-800-255-4101 +1-714-632-0882	www.us.zyxel.com	ZyXEL Communications Inc. 1130 N. Miller St. Anaheim CA 92806-2001 U.S.A.
	sales@zyxel.com	+1-714-632-0858	ftp.us.zyxel.com	
NORWAY	support@zyxel.no	+47-22-80-61-80	www.zyxel.no	ZyXEL Communications A/S Niils Hansens vei 13 0667 Oslo Norway
	sales@zyxel.no	+47-22-80-61-81		

METHOD LOCATION	SUPPORT E-MAIL	TELEPHONE ^A	WEB SITE	REGULAR MAIL
	SALES E-MAIL	FAX	FTP SITE	
POLAND	info@pl.zyxel.com	+48-22-5286603	www.pl.zyxel.com	ZyXEL Communications ul.Emilli Plater 53 00-113 Warszawa Poland
		+48-22-5206701		
RUSSIA	http://zyxel.ru/support	+7-095-542-89-29	www.zyxel.ru	ZyXEL Russia Ostrovityanova 37a Str. Moscow, 117279 Russia
	sales@zyxel.ru	+7-095-542-89-25		
SPAIN	support@zyxel.es	+34-902-195-420	www.zyxel.es	ZyXEL Communications Alejandro Villegas 33 1º, 28043 Madrid Spain
	sales@zyxel.es	+34-913-005-345		
SWEDEN	support@zyxel.se	+46-31-744-7700	www.zyxel.se	ZyXEL Communications A/S Sjöporten 4, 41764 Göteborg Sweden
	sales@zyxel.se	+46-31-744-7701		
UKRAINE	support@ua.zyxel.com	+380-44-247-69-78	www.ua.zyxel.com	ZyXEL Ukraine 13, Pimonenko Str. Kiev, 04050 Ukraine
	sales@ua.zyxel.com	+380-44-494-49-32		
UNITED KINGDOM	support@zyxel.co.uk	+44-1344 303044 08707 555779 (UK only)	www.zyxel.co.uk	ZyXEL Communications UK Ltd., 11 The Courtyard, Eastern Road, Bracknell, Berkshire, RG12 2XB, United Kingdom (UK)
	sales@zyxel.co.uk	+44-1344 303034	ftp.zyxel.co.uk	

A. "+" is the (prefix) number you enter to make an international telephone call.

Table of Contents

Copyright	3
Federal Communications Commission (FCC) Interference Statement	4
ZyXEL Limited Warranty	6
Customer Support.....	7
Table of Contents	9
List of Figures	13
List of Tables	15
Preface	17
Chapter 1	
Getting Started	19
1.1 About Your ZyXEL M-202	19
1.1.1 Application Overview	19
1.1.1.1 Infrastructure	19
1.1.1.2 Ad-Hoc	20
1.2 ZyXEL M-202 Hardware and Utility Installation	20
1.3 Configuration Methods	21
1.4 Windows XP Users Only	21
1.5 Accessing the ZyXEL Utility	21
1.6 ZyXEL Utility Screen Summary	22
1.7 Connecting to a Wireless LAN	22
1.7.1 Site Survey	23
1.7.2 Access Point Function	24
Chapter 2	
Wireless LAN Network.....	29
2.1 Wireless LAN Overview	29
2.1.1 SSID	29
2.1.2 Channel	29
2.1.3 Transmission Rate (Tx Rate)	29
2.2 Wireless LAN Security Overview	29
2.2.1 Data Encryption with WEP	30
2.2.2 IEEE 802.1x	30

2.2.2.1 EAP Authentication	30
2.2.3 WPA(2)	31
2.2.3.1 Encryption	31
2.2.3.2 User Authentication	31
2.2.4 WPA(2)-PSK Application Example	31
2.2.5 WPA(2) with RADIUS Application Example	32
2.3 Encryption Type	33
2.4 Preamble Type	33
Chapter 3	
ZyXEL Utility Configuration	35
3.1 The Link Info Screen	35
3.1.1 Trend Chart	36
3.2 The Site Survey Screen	37
3.2.1 Connecting to a WLAN Network	38
3.2.2 Security Settings	38
3.2.2.1 WEP Encryption	38
3.2.2.2 WPA/WPA2	39
3.2.2.3 WPA-PSK/WPA2-PSK	40
3.2.2.4 802.1x	41
3.2.3 Confirm Save Screen	42
3.3 The Profile Screen	43
3.3.1 Adding a New Profile	45
3.4 The Adapter Screen	48
Chapter 4	
Maintenance	51
4.1 The About Screen	51
4.2 Uninstalling the ZyXEL Utility	51
4.3 Upgrading the ZyXEL Utility	52
Chapter 5	
Troubleshooting	53
5.1 Problems Starting the ZyXEL Utility Program	53
5.2 Problem with the Link Status	53
5.3 Problems Communicating With Other Computers	54
Appendix A	
Product Specifications	55
Appendix B	
Disable Windows XP Wireless LAN Configuration Tool.....	57
Appendix C	

Management with Wireless Zero Configuration 63

Appendix D

Types of EAP Authentication 75

Index..... 79

List of Figures

Figure 1 Application: Infrastructure	20
Figure 2 Application: Ad-Hoc	20
Figure 3 ZyXEL Utility: System Tray Icon	21
Figure 4 Menu Summary	22
Figure 5 ZyXEL Utility: Site Survey	23
Figure 6 ZyXEL Utility: Security Settings	23
Figure 7 ZyXEL Utility: Link Info	24
Figure 8 ZyXEL AP-Mode Utility: Link Info	24
Figure 9 ZyXEL AP-Mode Utility: Configuration	25
Figure 10 ZyXEL AP-Mode Utility: MAC Filter	26
Figure 11 WPA(2)-PSK Authentication	32
Figure 12 WPA(2) with RADIUS Application Example	32
Figure 13 Link Info	35
Figure 14 Link Info: Trend Chart	36
Figure 15 Site Survey	37
Figure 16 Security Settings: WEP	38
Figure 17 Security Settings: WPA/WPA2	40
Figure 18 Security Settings: WPA-PSK/WPA2-PSK	41
Figure 19 Security Settings: 802.1x	41
Figure 20 Confirm Save Screen	42
Figure 21 Profile Screen	44
Figure 22 Profile: Add New Profile	45
Figure 23 Profile: Wireless Setting: Select a Channel	46
Figure 24 Profile: Security Setting: Encryption Type	47
Figure 25 Profile: Security Setting	47
Figure 26 Profile: Confirm New Settings	48
Figure 27 Profile: Activate the Profile	48
Figure 28 Adapter Screen	48
Figure 29 About	51
Figure 30 Uninstall: Finish	52
Figure 31 Windows XP: System Tray Icon	57
Figure 32 Windows XP SP1: Wireless Network Connection	58
Figure 33 Windows XP SP2: Wireless Network Connection	58
Figure 34 Windows XP SP1: Wireless Network Connection Properties	59
Figure 35 Windows XP SP2: Wireless Network Connection Properties	59
Figure 36 Windows XP SP1: Wireless Network Connection Status	60
Figure 37 Windows XP SP2: Wireless Network Connection Status	60
Figure 38 Windows XP SP1: Wireless Network Connection Properties	61

Figure 39 Windows XP SP2: Wireless Network Connection Properties	61
Figure 40 Windows XP SP2: WZC Not Available	63
Figure 41 Windows XP SP2: System Tray Icon	64
Figure 42 Windows XP SP2: Wireless Network Connection Status	64
Figure 43 Windows XP SP1: Wireless Network Connection Status	65
Figure 44 Windows XP SP2: Wireless Network Connection	65
Figure 45 Windows XP SP1: Wireless Network Connection Properties	66
Figure 46 Windows XP SP2: Wireless Network Connection: WEP or WPA-PSK ..	67
Figure 47 Windows XP SP2: Wireless Network Connection: No Security	67
Figure 48 Windows XP: Wireless (network) properties: Association	67
Figure 49 Windows XP: Wireless (network) properties: Authentication	69
Figure 50 Windows XP: Protected EAP Properties	70
Figure 51 Windows XP: Smart Card or other Certificate Properties	71
Figure 52 Windows XP SP2: Wireless Networks: Preferred Networks	73
Figure 53 Windows XP SP1: Wireless Networks: Preferred Networks	74

List of Tables

Table 1 ZyXEL Utility: System Tray Icon	21
Table 2 ZyXEL Utility: Menu Screen Summary	22
Table 3 ZyXEL AP Mode Utility: Status Screen Summary	25
Table 4 ZyXEL AP Mode Utility: Wireless & Security Settings	26
Table 5 ZyXEL AP Mode Utility: MAC Filter Menu	27
Table 6 Link Info	35
Table 7 Link Info: Trend Chart	36
Table 8 Site Survey	37
Table 9 Security Settings: WEP	39
Table 10 Security Settings: WPA/WPA2	40
Table 11 Security Settings: WPA-PSK/WPA2-PSK	41
Table 12 Security Settings: 802.1x	42
Table 13 Confirm Save Screen	43
Table 14 Profile Screen	44
Table 15 Profile: Add New Profile	45
Table 16 Profile: Wireless Setting: Select a Channel	46
Table 17 Adapter	49
Table 18 About	51
Table 19 Troubleshooting Starting ZyXEL Utility Program	53
Table 20 Troubleshooting Link Quality	53
Table 21 Troubleshooting Communication Problem	54
Table 22 Product Specifications	55
Table 23 Windows XP SP2: System Tray Icon	64
Table 24 Windows XP SP2: Wireless Network Connection	66
Table 25 Windows XP: Wireless Networks	67
Table 26 Windows XP: Wireless (network) properties: Association	68
Table 27 Windows XP: Wireless (network) properties: Authentication	69
Table 28 Windows XP: Protected EAP Properties	71
Table 29 Windows XP: Smart Card or other Certificate Properties	72
Table 30 Comparison of EAP Authentication Types	76
Table 31 Wireless Security Relational Matrix	78

Preface

Congratulations on your purchase of the ZyXEL M-202 802.11g Wireless USB 2.0 Adapter.

Your ZyXEL M-202 is easy to install and configure.

About This User's Guide

This manual is designed to guide you through the configuration of your ZyXEL M-202 for its various applications.

Related Documentation

- Supporting Disk

Refer to the included CD for support documents.

- Quick Start Guide

The Quick Start Guide is designed to help you get up and running right away. They contain hardware installation/connection information.

- ZyXEL Glossary and Web Site

Please refer to www.zyxel.com for an online glossary of networking terms and additional support documentation.











User Guide Feedback

Help us help you. E-mail all User Guide-related comments, questions or suggestions for improvement to techwriters@zyxel.com.tw or send regular mail to The Technical Writing Team, ZyXEL Communications Corp., 6 Innovation Road II, Science-Based Industrial Park, Hsinchu, 300, Taiwan. Thank you.

Syntax Conventions

- “Enter” means for you to type one or more characters. “Select” or “Choose” means for you to use one predefined choice.
- Mouse action sequences are denoted using a comma. For example, “In Windows, click **Start**, **Settings** and then **Control Panel**” means first click the **Start** button, then point your mouse pointer to **Settings** and then click **Control Panel**.
- “e.g.” is a shorthand for “for instance”, and “i.e.” means “that is” or “in other words”.
- The ZyXEL M-202 802.11g Wireless USB 2.0 Adapter may be referred to as the ZyXEL M-202 in this user's guide.

Graphics Icons Key

Wireless Access Point 	Computer 	Notebook Computer 
Server 	Modem 	Wireless Signal 
Telephone 	Switch 	Router 
Internet Cloud 		

CHAPTER 1

Getting Started

This chapter introduces the ZyXEL M-202 and prepares you to use the ZyXEL Utility.

1.1 About Your ZyXEL M-202

The ZyXEL M-202 is an IEEE 802.11g compliant wireless LAN USB adapter.

The following lists the main features of your ZyXEL M-202. See the product specifications in the appendix for detailed features.

- MIMO Smart Antenna technology for enhanced range, coverage, and speeds
- Automatic rate selection.
- Security: WEP (Wired Equivalent Privacy), IEEE 802.1x, WPA-PSK, WPA (Wi-Fi Protected Access), WPA2-PSK and WPA2

Note: WPA2 and WPA2-PSK are only available in Windows XP and Windows 2000.


- A built-in antenna
- Driver and utility support for Windows 2000 and Windows XP.

1.1.1 Application Overview

This section describes some network applications for the ZyXEL M-202.

1.1.1.1 Infrastructure


To connect to a network via an Access Point (AP), set the ZyXEL M-202 network type to **Infrastructure**. Through the AP, you can access the Internet or the wired network behind the AP.

Figure 1 Application: Infrastructure

1.1.1.2 Ad-Hoc

In case you prefer to set up a small independent wireless workgroup without an AP, use the Ad-Hoc mode.

Ad-hoc mode does not require an AP or a wired network. Two or more wireless clients communicate directly to each other.

Figure 2 Application: Ad-Hoc

1.2 ZyXEL M-202 Hardware and Utility Installation

Follow the instructions in the Quick Start Guide to install the ZyXEL Utility and make hardware connections.

1.3 Configuration Methods

To configure your ZyXEL M-202, use one of the following applications:

- Wireless Zero Configuration (WZC) (recommended for Windows XP)
- ZyXEL Utility (This guide shows you how to configure the ZyXEL M-202 using the ZyXEL Utility)
- Odyssey Client Manager (not supplied)

Refer to the Odyssey Client Manager documentation for more information.

Note: Do NOT use WZC or the Odyssey Client Manager and the ZyXEL Utility at the same time.

1.4 Windows XP Users Only

You must disable WZC if you want to use the ZyXEL utility. Refer to the appendices on how to deactivate WZC or how to use WZC to manage the ZyXEL M-202.

Note: When you use the ZyXEL Utility, it automatically disables the Windows XP wireless configuration tool.

1.5 Accessing the ZyXEL Utility

After you install and start the ZyXEL Utility, an icon for the ZyXEL Utility appears in the system tray.

Note: When the ZyXEL Utility system tray icon displays, the ZyXEL M-202 is installed properly.

When you use the ZyXEL Utility, it automatically disables the Windows XP wireless configuration tool.

Figure 3 ZyXEL Utility: System Tray Icon



The color of the ZyXEL Utility system tray icon indicates the status of the ZyXEL M-202. Refer to the following table for details.

Table 1 ZyXEL Utility: System Tray Icon


COLOR	DESCRIPTION
Red	The ZyXEL M-202 is operating in wireless station mode but is not connected to a wireless network.
Green	The ZyXEL M-202 is operating in wireless station mode and connected to a wireless network.

Double-click on the ZyXEL Wireless LAN Utility icon in the system tray to open the ZyXEL Utility. The ZyXEL Utility screens are similar in all Microsoft Windows versions. Screens for Windows 2000 are shown.

1.6 ZyXEL Utility Screen Summary

This sections describes the ZyXEL Utility screens.

Figure 4 Menu Summary



The following table describes the menus.

Table 2 ZyXEL Utility: Menu Screen Summary

TAB	DESCRIPTION
Link Info	Use this screen to see your current connection status, configuration and data rate statistics.
Site Survey	Use this screen to <ul style="list-style-type: none">• scan for a wireless network• configure wireless security (if activated on the selected network).• connect to a wireless network.
Profile	Use this screen to add, delete, edit or activate a profile with a set of wireless and security settings.
Adapter	Use this screen to configure transfer rates and enable power saving modes.

1.7 Connecting to a Wireless LAN

The following sections show you how to associate with a network using the ZyXEL Utility. You can either manually connect to a network or configure a profile to have the ZyXEL M-202 automatically connect to a specific network. Otherwise, configure nothing and leave the ZyXEL M-202 to automatically scan for and connect to any other available network without security.


See the next chapters for detailed field descriptions.

1.7.1 Site Survey

After you install the ZyXEL Utility and then insert the ZyXEL M-202, follow the steps below to connect to a network using the Site Survey screen.

- 1 Make sure a wireless network is available and within range.
- 2 Open the ZyXEL Utility and click the **Site Survey** tab to open the screen as shown next.
- 3 Click **Scan** to search for available wireless networks.


Figure 5 ZyXEL Utility: Site Survey



- 4 To join a network, either click an SSID in the table and then click **Connect** or double-click an SSID.
- 5 If the wireless security is activated for the selected wireless network, the **Security Settings** screen displays. This screen varies according to the network's encryption method. Configure the same security settings as the associated network.


Note: If the selected network is unavailable or security settings are not correct, the ZyXEL M-202 will be disconnected.

Figure 6 ZyXEL Utility: Security Settings



- 6 Verify that you have successfully connected to the selected network and check the network information in the **Link Info** screen. If the ZyXEL M-202 is not connected to a network, the fields in this screen are blank.


Figure 7 ZyXEL Utility: Link Info



1.7.2 Access Point Function

Your ZyXEL M-202 is equipped with Access Point functionality using AP Mode. Please follow the steps below to configure your M-202 in AP Mode.

Figure 8 ZyXEL M-202 AP-Mode Utility



- 1 Click on the box next to the AP Mode to enable Access Point functionality on the M-202.


The following table describes the menus.

Table 3 ZyXEL AP Mode Utility: Status Screen Summary

TAB & LABELS	DESCRIPTION
Link Info	Use this screen to see your current connection status, configuration and data rate statistics.
Configuration	Use this screen to access and set your security and wireless settings.
MAC Filter	Use this screen to display and configure your MAC filtering for the M-202.
SSID	Displays the current SSID assigned to the M-202 in AP Mode
Current Channel	Displays the current channel assigned to the M-202 in AP Mode
Transmission Rate	Displays the current transmission rates for the M-202 in AP Mode
Security	Displays the security settings currently placed on the M-202 in AP Mode
MAC	Displays the current MAC address for the M-202 in AP Mode
Output Power	Shows the current Output Power settings for the M-202 in AP Mode

To alter configurations within your M-202 during Access Point mode, do so within the Configuration Tab menu.

Figure 9 ZyXEL Utility: AP Mode Configuration




The following table describes the menus.

Table 4 ZyXEL AP Mode Utility: Wireless & Security Settings

MENUS	DESCRIPTION
SSID	Use this screen to see your current connection status, configuration and data rate statistics.
Configuration	Use this screen to access and set your security and wireless settings.
MAC Filter	Use this screen to display and configure your MAC filtering for the M-202.
SSID	Displays the current SSID assigned to the M-202 in AP Mode
Current Channel	Displays the current channel assigned to the M-202 in AP Mode
Transmission Rate	Displays the current transmission rates for the M-202 in AP Mode
Security	Displays the security settings currently placed on the M-202 in AP Mode
MAC	Displays the current MAC address for the M-202 in AP Mode
Output Power	Shows the current Output Power settings for the M-202 in AP Mode

To alter MAC Address configurations within your M-202 during Access Point mode, do so within the MAC Filter Tab menu.

Figure 10 ZyXEL Utility: AP Mode MAC Address Filtering



The following table describes the menus.

Table 5 ZyXEL AP Mode Utility: Mac Filter Menu

MENUS	DESCRIPTION
Link Info	Use this screen to see your current connection status, configuration and data rate statistics.
Configuration	Use this screen to access and set your security and wireless settings.
MAC Filter	Use this screen to display and configure your MAC filtering for the M-202.
Filter Type	Use this pull down menu to select which type of MAC Address filtering you wish to employ
Filter MAC Address	Use this text area to manually type in MAC addresses you wish to filter

CHAPTER 2

Wireless LAN Network

This chapter provides background information on wireless LAN network.

2.1 Wireless LAN Overview

This section describes the wireless LAN network terms and applications.

2.1.1 SSID

The SSID (Service Set Identity) is a unique name shared among all wireless devices in a wireless network. Wireless devices must have the same SSID to communicate with each other.

2.1.2 Channel

A radio frequency used by a wireless device is called a channel.

2.1.3 Transmission Rate (Tx Rate)

The ZyXEL M-202 provides various transmission (data) rate options for you to select. Options include **Fully Auto**, **1 Mbps**, **2 Mbps**, **5.5 Mbps**, **6 Mbps**, **9 Mbps**, **11 Mbps**, **12 Mbps**, **18 Mbps**, **24 Mbps**, **36 Mbps**, **48 Mbps** and **54 Mbps**. In most networking scenarios, the factory default **Fully Auto** setting proves the most efficient. This setting allows your ZyXEL M-202 to operate at the maximum transmission (data) rate. When the communication quality drops below a certain level, the ZyXEL M-202 automatically switches to a lower transmission (data) rate. Transmission at lower data speeds is usually more reliable. However, when the communication quality improves again, the ZyXEL M-202 gradually increases the transmission (data) rate again until it reaches the highest available transmission rate. You can select any of the above options. If you wish to balance speed versus reliability, select **54 Mbps** in a networking environment where you are certain that all wireless devices can communicate at the highest transmission (data) rate. **1 Mbps** or **2 Mbps** are used often in networking environments where the range of the wireless connection is more important than speed.

Note: With USB1.0/1.1, the ZyXEL M-202 can only transmit at up to 11Mbps.

Actual speeds attained also depend on the distance from the AP, noise, etc.

2.2 Wireless LAN Security Overview

Wireless LAN security is vital to your network to protect wireless communications.

Configure the wireless LAN security using the **Profile Security Setting** screen. If you do not enable any wireless security on your ZyXEL M-202, the ZyXEL M-202's wireless communications are accessible to any wireless networking device that is in the coverage area.

2.2.1 Data Encryption with WEP

WEP (Wired Equivalent Privacy) encryption scrambles all data packets transmitted between the ZyXEL M-202 and the AP or other wireless stations to keep network communications private. Both the wireless stations and the access points must use the same WEP key for data encryption and decryption.

There are two ways to create WEP keys in your ZyXEL M-202.

- Automatic WEP key generation based on a “password phrase” called a passphrase. The passphrase is case sensitive. You must use the same passphrase for all WLAN adapters with this feature in the same WLAN.

For WLAN adapters without the passphrase feature, you can still take advantage of this feature by writing down the four automatically generated WEP keys from the **Security Setting** screen of the ZyXEL Utility and entering them manually as the WEP keys in the other WLAN adapter(s).

- Enter the WEP keys manually.

Your ZyXEL M-202 allows you to configure up to four 64-bit, 128-bit or 256-bit WEP keys and only one key is used as the default key at any one time.

2.2.2 IEEE 802.1x

The IEEE 802.1x standard outlines enhanced security methods for both the authentication of wireless stations and encryption key management. Authentication can be done using an external RADIUS server.

2.2.2.1 EAP Authentication

EAP (Extensible Authentication Protocol) is an authentication protocol that runs on top of the IEEE 802.1x transport mechanism in order to support multiple types of user authentication. By using EAP to interact with an EAP-compatible RADIUS server, an access point helps a wireless station and a RADIUS server perform authentication.

The type of authentication you use depends on the RADIUS server and an intermediary AP(s) that supports IEEE 802.1x. The ZyXEL M-202 supports EAP-TLS and EAP-PEAP. Refer to [Appendix D on page 75](#) for descriptions.

For EAP-TLS authentication type, you must first have a wired connection to the network and obtain the certificate(s) from a certificate authority (CA). A certificate (also called digital IDs) can be used to authenticate users and a CA issues certificates and guarantees the identity of each certificate owner.

2.2.3 WPA(2)

Wi-Fi Protected Access (WPA) is a subset of the IEEE 802.11i standard. WPA2 (IEEE 802.11i) is a wireless security standard that defines stronger encryption, authentication and key management than WPA.

Key differences between WPA(2) and WEP are improved data encryption and user authentication.

If both an AP and the wireless clients support WPA2 and you have an external RADIUS server, use WPA2 for stronger data encryption. If you don't have an external RADIUS server, you should use WPA2-PSK (WPA2-Pre-Shared Key) that only requires a single (identical) password entered into each access point, wireless gateway and wireless client. As long as the passwords match, a wireless client will be granted access to a WLAN.

If the AP or the wireless clients do not support WPA2, just use WPA or WPA-PSK depending on whether you have an external RADIUS server or not.

Select WEP only when the AP and/or wireless clients do not support WPA or WPA2. WEP is less secure than WPA or WPA2.

2.2.3.1 Encryption

Both WPA and WPA2 improve data encryption by using Temporal Key Integrity Protocol (TKIP), Message Integrity Check (MIC) and IEEE 802.1x. In addition to TKIP, WPA2 also uses Advanced Encryption Standard (AES) in the Counter mode with Cipher block chaining Message authentication code Protocol (CCMP) to offer stronger encryption.

The encryption mechanisms used for WPA(2) and WPA(2)-PSK are the same. The only difference between the two is that WPA(2)-PSK uses a simple common password, instead of user-specific credentials. The common-password approach makes WPA(2)-PSK susceptible to brute-force password-guessing attacks but it's still an improvement over WEP as it employs an easier-to-use, consistent, single, alphanumeric password.

2.2.3.2 User Authentication

WPA or WPA2 applies IEEE 802.1x and Extensible Authentication Protocol (EAP) to authenticate wireless clients using an external RADIUS database.

2.2.4 WPA(2)-PSK Application Example

A WPA(2)s-PSK application looks as follows.

- 1 First enter identical passwords into the AP and all wireless clients. The Pre-Shared Key (PSK) must consist of between 8 and 63 ASCII characters (including spaces and symbols).
- 2 The AP checks each client's password and (only) allows it to join the network if it matches its password.

- 3 The AP derives and distributes keys to the wireless clients.
- 4 The AP and wireless clients use the TKIP or AES encryption process to encrypt data exchanged between them.

Figure 11 WPA(2)-PSK Authentication




2.2.5 WPA(2) with RADIUS Application Example

You need the IP address of the RADIUS server, its port number (default is 1812), and the RADIUS shared secret. A WPA(2)-RADIUS application example with an external RADIUS server looks as follows. "A" is the RADIUS server. "DS" is the distribution system.

- 1 The AP passes the wireless client's authentication request to the RADIUS server.
- 2 The RADIUS server then checks the user's identification against its database and grants or denies network access accordingly.
- 3 The RADIUS server distributes a Pairwise Master Key (PMK) key to the AP that then sets up a key hierarchy and management system, using the pair-wise key to dynamically generate unique data encryption keys to encrypt every data packet that is wirelessly communicated between the AP and the wireless clients.

Figure 12 WPA(2) with RADIUS Application Example



2.3 Encryption Type

The IEEE 802.11b/g standard describes a simple encryption method between the wireless stations and AP. Two encryption types are defined: an **Open** system mode and a **Shared** key mode.

- **Open** system mode is implemented for ease-of-use and when security is not an issue. The wireless station and the AP do *not* share a secret key. Thus the wireless stations can associate with any AP and listen to any data transmitted plaintext.
- **Shared** key mode involves a shared secret key to authenticate the wireless station to the AP. This requires you to enable the wireless LAN security and use same settings on both the wireless station and the AP.

2.4 Preamble Type

Preamble is used to signal that data is coming to the receiver.

Short preamble increases performance as less time sending preamble means more time for sending data. All IEEE 802.11b/g compliant wireless adapters support long preamble, but not all support short preamble.

Select **Long** preamble if you are unsure what preamble mode the wireless adapters support, and to provide more reliable communications in busy wireless networks.

Select **Long and Short** to have the ZyXEL M-202 automatically use short preamble when access point/wireless stations support it, otherwise the ZyXEL M-202 uses long preamble.

Note: The ZyXEL M-202 and the access point/wireless stations **MUST** use the same preamble mode in order to communicate.

CHAPTER 3


ZyXEL Utility Configuration

This chapter shows you how to configure your ZyXEL M-202 in wireless station mode.

3.1 The Link Info Screen

When the ZyXEL Utility starts, the **Link Info** screen displays, showing the current configuration and connection status of your ZyXEL M-202.

Figure 13 Link Info



The following table describes the labels in this screen.

Table 6 Link Info


LABEL	DESCRIPTION
Wireless Network Status	
Profile Name	This is the name of the profile you are currently using.
Network Name (SSID)	The SSID identifies the Service Set to which a wireless station is associated. This field displays the name of the wireless device to which the ZyXEL M-202 is associated.
AP MAC Address	This field displays the MAC address of the wireless device to which the ZyXEL M-202 is associated.
Network Type	This field displays the network type (Infrastructure(BSS) or Ad Hoc) of the wireless network.
Transmission Rate	This field displays the current transmission rate of the ZyXEL M-202 in megabits per second (Mbps).

Table 6 Link Info (continued)

LABEL	DESCRIPTION
Security	This field displays whether data encryption is activated (WEP (WEP or 802.1x), TKIP (WPA/WPA-PSK), AES (WPA2/WPA2-PSK)) or inactive (DISABLE).
Channel	This field displays the radio channel the ZyXEL M-202 is currently using.
Statistics	
Transmit Rate	This field displays the current data transmission rate in kilobits per second (Kbps).
Receive Rate	This field displays the current data receiving rate in kilobits per second (Kbps).
Authentication	This field displays the authentication method of the ZyXEL M-202.
Network Mode	This field displays the network standard (B or G) of the wireless device.
Total Transmit	This field displays the total number of data frames transmitted.
Total Receive	This field displays the total number of data frames received.
Link Quality	This field displays the quality of the signal of the ZyXEL M-202.
Trend Chart	Click this button to display the real-time statistics of the data rate in kilobits per second (Kbps).
Signal Strength	The status bar shows the strength of the signal.
Link Quality	The status bar shows the quality of the signal.

3.1.1 Trend Chart

Click **Trend Chart** in the **Link Info** screen to display a screen as shown below. Use this screen to view real-time data traffic statistics.

Figure 14 Link Info: Trend Chart

The following table describes the labels in this screen.


Table 7 Link Info: Trend Chart

LABEL	DESCRIPTION
Transmit	This field displays the current data transmission rate in kilobits per second (Kbps).
Receive	This field displays the current data receiving rate in kilobits per second (Kbps).

3.2 The Site Survey Screen

Use the **Site Survey** screen to scan for and connect to a wireless network automatically.

Figure 15 Site Survey



The following table describes the labels in this screen.

Table 8 Site Survey

LABEL	DESCRIPTION
Available Network List	Click a column heading to sort the entries.
, , or 	denotes that the wireless device is in infrastructure mode and the wireless security is activated. denotes that the wireless device is in infrastructure mode but the wireless security is deactivated. denotes that the wireless device is in Ad-Hoc mode and the wireless security is activated. denotes that the wireless device is in Ad-Hoc mode but the wireless security is deactivated.
SSID	This field displays the SSID (Service Set IDentifier) of each wireless device.
Channel	This field displays the channel number used by each wireless device.
Signal	This field displays the signal strength of each wireless device.
Scan	Click Scan to search for available wireless devices within transmission range.
Connect	Click Connect to associate to the selected wireless device.
Site Information	Click an entry in the Available Network List table to display the information of the selected wireless device.
Network Type	This field displays the network type (Infrastructure or Ad Hoc) of the wireless device.
Channel	This field displays the channel number used by each wireless device.
Security	This field shows whether data encryption is activated (WEP (WEP or 802.1x), WPA , WPA-PSK , WPA2 , WPA2-PSK) or inactive (DISABLE).

Table 8 Site Survey (continued)

LABEL	DESCRIPTION
MAC address	This field displays the MAC address of the wireless device.
Surveyed at	This field displays the time when the wireless device is scanned.

3.2.1 Connecting to a WLAN Network

Follow the steps below to connect to a WLAN network using the **Site Survey** screen.


- 1 Click **Scan** to search for all available wireless networks within range.
- 2 To join a network, click an entry in the table to select a wireless network and then click **Connect**.
- 3 If the WEP encryption is activated for the selected wireless network, the **Security Setting** screen displays. You must set the related fields in the **Security Setting** screen to the same security settings as the associated wireless device. Refer to [Section 3.2.2 on page 38](#) for more information.

Otherwise click the **Back** or **Exit** button and connect to another wireless network without data encryption.
- 4 Verify that you have successfully connected to the selected network and check the network information in the **Link Info** screen.

3.2.2 Security Settings

When you configure the ZyXEL M-202 to connect to a network with wireless security activated and the security settings are disabled on the ZyXEL M-202, the screen varies according to the encryption method used by the selected network.

3.2.2.1 WEP Encryption

Figure 16 Security Settings: WEP

The screenshot shows the 'Security Setting' window with a blue title bar. It contains five configuration items, each with a yellow star icon: 'WEP:' with a dropdown menu set to '64 bits'; 'Encryption Type:' with a dropdown menu set to 'Open'; 'Pass Phrase:' with an empty text input field; 'Transmit Key:' with a dropdown menu set to '1'; and 'Key1:' with an empty text input field. At the bottom right, there are three buttons: 'Back', 'Next', and 'Exit'.

The following table describes the labels in this screen.

Table 9 Security Settings: WEP

LABEL	DESCRIPTION
Security Setting	
WEP	Select 64 Bits , 128 Bits or 256 Bits to activate WEP encryption and then fill in the related fields. Select Disable to deactivate WEP encryption.
Encryption Type	Select an encryption type. Choices are Open and Shared . Refer to Section 2.3 on page 33 for more information.
Pass Phrase	When you select the radio button, enter a passphrase of up to 63 case-sensitive printable characters. As you enter the passphrase, the ZyXEL M-202 automatically generates four different WEP keys and displays it in the key field below. Refer to Section 2.2.1 on page 30 for more information.
Transmit Key	Select a default WEP key to use for data encryption. The key displays in the field below.
Key x (where x is a number between 1 and 4)	Select this option if you want to manually enter the WEP keys. Enter the WEP key in the field provided. If you select 64 Bits in the WEP field. Enter either 10 hexadecimal digits in the range of "A-F", "a-f" and "0-9" (for example, 11AA22BB33) for HEX key type. or Enter 5 ASCII characters (case sensitive) ranging from "a-z", "A-Z" and "0-9" (for example, MyKey) for ASCII key type. If you select 128 Bits in the WEP field, Enter either 26 hexadecimal digits in the range of "A-F", "a-f" and "0-9" (for example, 00112233445566778899AABBCC) for HEX key type or Enter 13 ASCII characters (case sensitive) ranging from "a-z", "A-Z" and "0-9" (for example, MyKey12345678) for ASCII key type. If you select 256 Bits in the WEP field, Enter either 64 hexadecimal digits in the range of "A-F", "a-f" and "0-9" (for example, 0000111122223333444455556666777788889999AAAA BBBBCCCCDDDD EEEFFF) for HEX key type or Enter 32 ASCII characters (case sensitive) ranging from "a-z", "A-Z" and "0-9" (for example, MyKey123456789011234567890123456) for ASCII key type. Note: The values for the WEP keys must be set up exactly the same on all wireless devices in the same wireless LAN. ASCII WEP keys are case sensitive.
Back	Click Back to go to the Site Survey screen to select and connect to other network.
Next	Click Next to confirm your selections and advance to the Confirm Save screen. Refer to Section 3.2.3 on page 42 .
Exit	Click Exit to return to the Site Survey screen without saving.

3.2.2.2 WPA/WPA2

Note: WPA2 and WPA2-PSK are only available in Windows XP and Windows 2000.

Figure 17 Security Settings: WPA/WPA2

The following table describes the labels in this screen.

Table 10 Security Settings: WPA/WPA2

LABEL	DESCRIPTION
Authentication Type	Select an authentication method from the drop down list. Options are TLS , TTLS and PEAP .
Login Name	Enter a user name. This is the user name that you or an administrator set up on a WPA/WPA2 server.
Password	This field is not available when you select TLS in the Authentication Type field. Enter the password associated with the user name above.
Certificate	This field is only available when you select TLS in the Authentication Type field. Select a certificate from the drop-down list box. Note: You must first have a wired connection to a network and obtain the certificate(s) from a certificate authority (CA). Consult your network administrator for more information.
Server CA	Select the server certificate or select <Trust Any> as default.
PEAP Inner EAP	This field is only available when you select PEAP in the Authentication Type field. The PEAP protocol is MS CHAP v2 .
Back	Click Back to go to the Site Survey screen to select and connect to other network.
Next	Click Next to confirm your selections and advance to the Confirm Save screen. Refer to Section 3.2.3 on page 42 .
Exit	Click Exit to return to the Site Survey screen without saving.

3.2.2.3 WPA-PSK/WPA2-PSK

Note: WPA2 and WPA2-PSK are only available in Windows XP and Windows 2000.

Figure 18 Security Settings: WPA-PSK/WPA2-PSK

The following table describes the labels in this screen.

Table 11 Security Settings: WPA-PSK/WPA2-PSK

LABEL	DESCRIPTION
Security Setting	
Encryption Type	The encryption mechanisms used for WPA/WPA2 and WPA-PSK/WPA2-PSK are the same. The only difference between the two is that WPA-PSK/WPA2-PSK uses a simple common password, instead of user-specific credentials. The encryption types for WPA-PSK and WPA2-PSK are TKIP and AES respectively. Refer to Section 2.2.3 on page 31 for more information.
Pass Phrase	Type a passphrase from 8 to 63 case-sensitive ASCII characters (including spaces and symbols).
Back	Click Back to go to the Site Survey screen to select and connect to other network.
Next	Click Next to confirm your selections and advance to the Confirm Save screen. Refer to Section 3.2.3 on page 42 .
Exit	Click Exit to return to the Site Survey screen without saving.

3.2.2.4 802.1x

Figure 19 Security Settings: 802.1x

The following table describes the labels in this screen.

Table 12 Security Settings: 802.1x

LABEL	DESCRIPTION
Authentication Type	Select an authentication method from the drop down list. Options are TLS , TTLS and PEAP .
Login Name	Enter a user name. This is the user name that you or an administrator set up on a RADIUS server.
Password	This field is not available when you select TLS in the Authentication Type field. Enter the password associated with the user name above.
Certificate	This field is only available when you select TLS in the Authentication Type field. Select a certificate from the drop-down list box. Note: You must first have a wired connection to a network and obtain the certificate(s) from a certificate authority (CA). Consult your network administrator for more information.
Server CA	Select the server certificate or select <Trust Any> as default.
PEAP Inner EAP	This field is only available when you select PEAP in the Authentication Type field. The PEAP protocol is MS CHAP v2 .
Back	Click Back to go to the Site Survey screen to select and connect to other network.
Next	Click Next to confirm your selections and advance to the Confirm Save screen. Refer to Section 3.2.3 on page 42 .
Exit	Click Exit to return to the Site Survey screen without saving.

3.2.3 Confirm Save Screen

Use the **Confirm Save** screen to confirm and save the security settings.

Figure 20 Confirm Save Screen

The screenshot shows the 'Confirm Save' screen with a blue header bar. Below the header, the following settings are displayed:

- Network Name(SSID): Test
- Network Type: Infrastructure
- Network Mode: 2.4 GHz
- Channel: Auto
- Security: DISABLE

At the bottom right, there are three buttons: 'Back', 'Save', and 'Exit'.

The following table describes the labels in this screen.

Table 13 Confirm Save Screen

LABEL	DESCRIPTION
Security Setting	
Network Name	This field displays the SSID previously entered.
Network Type	This field displays the network type (Infrastructure or Ad Hoc) of the wireless device.
Channel	This field displays the channel number used by the profile.
Security	This field shows whether data encryption is activated (WEP , WPA , WPA2 , WPA-PSK , WPA2-PSK or 802.1x) or inactive (DISABLE).
Back	Click Back to return to the Encryption/Authentication screen
Save	Click Save to save the changes back to the ZyXEL M-202 and display the Link Info screen. Otherwise, click Back to go back to the Encryption Type screen or click Exit to discard changes and go back to the Site Survey screen.
Exit	Click Exit to discard changes and return to the Site Survey screen.

3.3 The Profile Screen


A profile is a set of wireless parameters that you need to connect to a wireless network. With a profile activated, each time you start the ZyXEL M-202, it automatically scans for the specific SSID and joins that network with the pre-defined wireless security settings. If the specified network is not available, the ZyXEL M-202 will be disconnected.

If you do not configure and activate a profile, each time you start the ZyXEL M-202, the ZyXEL M-202 uses the default profile to connect to any available network with security disabled.

The default profile is a profile that allows you to connect to any SSID without security.

Click the **Profile** tab in the ZyXEL Utility program to display the **Profile** screen as shown next.

The profile function allows you to save the wireless network settings in this screen, or use one of the pre-configured network profiles.

Figure 21 Profile Screen

The following table describes the labels in this screen.

Table 14 Profile Screen

LABEL	DESCRIPTION
Profile List	Click a column heading to sort the entries.
, , or , 	denotes that the wireless device is in infrastructure mode and the wireless security is activated. denotes that the wireless device is in infrastructure mode but the wireless security is deactivated. denotes that the wireless device is in Ad-Hoc mode and the wireless security is activated. denotes that the wireless device is in Ad-Hoc mode but the wireless security is deactivated.
Profile Name	This is the name of the pre-configured profile.
SSID	This is the SSID of the wireless network to which the selected profile associate.
Connect	To use a previously saved network profile, select a pre-configured profile name in the table and click Connect .
Add	To add a new profile into the table, click Add .
Delete	To delete an existing wireless network configuration, select a profile in the table and click Delete .
Edit	To edit an existing wireless network configuration, select a profile in the table and click Edit .
Profile Info	The following fields display detail information of the selected profile in the Profile List table.
Network Type	This field displays the network type (Infrastructure or Ad Hoc) of the profile.
SSID	This field displays the SSID (Service Set IDentifier) of the profile.
Channel	This field displays the channel number used by the profile.

Table 14 Profile Screen (continued)

LABEL	DESCRIPTION
Security	This field shows whether data encryption is activated (WEP (WEP or 802.1x), WPA , WPA-PSK , WPA2 , WPA2-PSK) or inactive (DISABLE).
Transfer Rate	This field displays the transfer speed of the selected profile in megabits per second (Mbps).

3.3.1 Adding a New Profile

Follow the steps below to add a new profile.

- 1 Click **Add** in the **Profile** screen. An **Add New Profile** screen displays as shown next. Click **Next** to continue.









Figure 22 Profile: Add New Profile

The following table describes the labels in this screen.


Table 15 Profile: Add New Profile

LABEL	DESCRIPTION
Add New Profile	
Profile Name	Enter a descriptive name in this field.
SSID	Select an available wireless device in the Scan Info table and click Select , or enter the SSID of the wireless device to which you want to associate in this field manually. Otherwise, enter Any to have the ZyXEL M-202 associate to or roam between any infrastructure wireless networks.
Network Type	Select the Infrastructure radio button to associate to an AP. Select the Ad-Hoc radio button to associate to a peer computer.
Next	Click Next to go to the next screen.
Exit	Click Exit to go back to the previous screen without saving.
Scan Info	This table displays the information of the available wireless networks within the transmission range.

Table 15 Profile: Add New Profile (continued)

LABEL	DESCRIPTION
 ,  , or  	 denotes that the wireless device is in infrastructure mode and the wireless security is activated.  denotes that the wireless device is in infrastructure mode but the wireless security is deactivated.  denotes that the wireless device is in Ad-Hoc mode and the wireless security is activated.  denotes that the wireless device is in Ad-Hoc mode but the wireless security is deactivated.
SSID	This field displays the SSID (Service Set Identifier) of each wireless device.
Scan	Click Scan to search for available wireless devices within transmission range.
Select	Select an available wireless device in the table and click Select to add it to this profile. Whenever you activate this profile, the ZyXEL M-202 associates to the selected wireless network only.

- 2** If you select the **Infrastructure** network type in the previous screen, skip to step **3**. If you select the **Ad-Hoc** network type in the previous screen, a screen displays as follows. Select a channel number and click **Next** to continue.

Figure 23 Profile: Wireless Setting: Select a Channel

The following table describes the labels in this screen.

Table 16 Profile: Wireless Setting: Select a Channel

LABEL	DESCRIPTION
Wireless Setting	
Channel	Select a channel number from the drop-down list box. To associate to an ad-hoc network, you must use the same channel as the peer computer.
Back	Click Back to return to the Add New Profile screen.
Next	Click Next to confirm your selection and advance to the Encryption Type screen.
Exit	Click Exit to discard changes and return to the Add New Profile screen.

- 3 If you select **Infrastructure** network type in the first screen, select **WEP**, **WPA**, **WPA2**, **WPA-PSK**, **WPA2-PSK** or **802.1x** from the drop-down list box to enable data encryption. If you select **Ad-Hoc** network type in the first screen, you can only use **WEP** encryption method. Otherwise, select **DISABLE** to allow the ZyXEL M-202 to communicate with the access points or other peer wireless computers without any data encryption and skip to step 5.

Figure 24 Profile: Security Setting: Encryption Type

The screenshot shows a window titled "Security Setting" with a blue header bar. Below the header, there is a label "Encryption Type :" followed by a dropdown menu. The dropdown menu is open, showing a list of options: "DISABLE", "WEP", "WPA", "WPA2", "WPA-PSK", "WPA2-PSK", and "802.1x". The "DISABLE" option is currently selected and highlighted. At the bottom of the window, there are three buttons: "Back", "Next", and "Exit".

- 4 The screen varies depending on the encryption method you select in the previous screen. The settings must be exactly the same on the APs or other peer wireless computers as they are on the ZyXEL M-202. Refer to [Section 3.2.2 on page 38](#) for detailed information on wireless security configuration.

Figure 25 Profile: Security Setting

The screenshot shows a window titled "Security Setting" with a blue header bar. Below the header, there are several settings, each with a label and a corresponding input field or dropdown menu. The settings are: "WEP:" with a dropdown menu showing "64 bits"; "Encryption Type :" with a dropdown menu showing "Open"; "Pass Phrase:" with a text input field; "Transmit Key:" with a dropdown menu showing "1"; and "Key1:" with a text input field. At the bottom of the window, there are three buttons: "Back", "Next", and "Exit".

- 5 This read-only screen shows a summary of the new profile settings. Verify that the settings are correct. Click **Save** to save and go to the next screen. Click **Back** to return to the previous screen. Otherwise, click **Exit** to go back to the **Profile** screen without saving.

Figure 26 Profile: Confirm New Settings


A dialog box titled "Confirm Save" with a blue header bar. It contains a list of network settings with green expandable icons to the left of each label. The settings are: Network Name(SSID): Test, Network Type: Infrastructure, Network Mode: 2.4 GHz, Channel: Auto, and Security: DISABLE. At the bottom right, there are three buttons: "Back", "Save", and "Exit".

➤ Network Name(SSID):	Test
➤ Network Type:	Infrastructure
➤ Network Mode:	2.4 GHz
➤ Channel:	Auto
➤ Security:	DISABLE

Back Save Exit

6 To use this network profile, click the **Activate Now** button. Otherwise, click the **Activate Later** button.

Note: Once you activate a profile, the ZyXEL Utility will use that profile the next time it is started.

Figure 27 Profile: Activate the Profile


A message box with a blue header bar containing an exclamation mark icon. The text inside says "Your Network has been configured successfully!". At the bottom, there are two buttons: "Activate Now" and "Activate Later".

! Your Network has been configured successfully!

Activate Now Activate Later

3.4 The Adapter Screen

To set the advanced features on the ZyXEL M-202, click the **Adapter** tab.

Figure 28 Adapter Screen

A dialog box titled "Adapter Setting" with a blue header bar. It contains three settings with green expandable icons to the left of each label: Transfer Rate: Auto, Preamble Type: Auto, and Power Saving Mode: Continuous Access Mode. Each setting is followed by a dropdown arrow. At the bottom right, there is a "Save" button.

➤ Transfer Rate:	Auto
➤ Preamble Type:	Auto
➤ Power Saving Mode:	Continuous Access Mode

Save

The following table describes the labels in this screen.

Table 17 Adapter

LABEL	DESCRIPTION
Adapter Setting	
Transfer Rate	Select a transfer speed from the drop-down list box. Choose from Fully Auto (default), 1 Mbps , 2 Mbps , 5.5 Mbps , 6 Mbps , 9 Mbps , 12 Mbps , 18 Mbps , 24 Mbps , 36 Mbps , 48 Mbps and 54 Mbps .
Preamble Type	Select a preamble type. Choices are Auto , Long and Short . The default setting is Auto . Refer to Section 2.4 on page 33 for more information.
Power Saving Mode	Select FPS or MPS to save power (especially for notebook computers). This forces the ZyXEL M-202 to go to sleep mode when it is not transmitting data. When you select CAM , the ZyXEL M-202 will never go to sleep mode.
Save	Click Save to save the changes back to the ZyXEL M-202 and return to the Link Info screen.

CHAPTER 4

Maintenance

This chapter describes how to uninstall or upgrade the ZyXEL Utility.

4.1 The About Screen


The **About** screen displays related version numbers of the ZyXEL M-202. To display the screen as shown below, click the about () button.

Figure 29 About



The following table describes the read-only fields in this screen.


Table 18 About

LABEL	DESCRIPTION
Driver Version	This field displays the version number of the ZyXEL M-202 driver.
Utility Version	This field displays the version number of the ZyXEL Utility.

4.2 Uninstalling the ZyXEL Utility

Follow the steps below to remove (or uninstall) the ZyXEL Utility from your computer.

- 1 Click **Start, Programs, ZyXEL M-202 Client Utility, Uninstall ZyXEL M-202 Client Utility**.
- 2 Click **Finish** to complete uninstalling the software and restart the computer when prompted.

Figure 30 Uninstall: Finish

4.3 Upgrading the ZyXEL Utility

Note: Before you uninstall the ZyXEL Utility, take note of the current network configuration.

To perform the upgrade, follow the steps below.

- 1 Download the latest version of the utility from the ZyXEL web site and save the file on your computer.
- 2 Follow the steps in [Section 4.2 on page 51](#) to remove the current ZyXEL Utility from your computer.
- 3 Restart your computer when prompted.
- 4 Disconnect the ZyXEL M-202 from your computer.
- 5 Double-click on the setup program for the new utility to start the ZyXEL Utility installation.
- 6 Insert the ZyXEL M-202 and check the version numbers in the **About** screen to make sure the new utility is installed properly

CHAPTER 5

Troubleshooting

This chapter covers potential problems and the possible remedies. After each problem description, some instructions are provided to help you to diagnose and to solve the problem.

5.1 Problems Starting the ZyXEL Utility Program

Table 19 Troubleshooting Starting ZyXEL Utility Program

PROBLEM	CORRECTIVE ACTION
Cannot start the ZyXEL Wireless LAN Utility	<p>Make sure the ZyXEL M-202 is properly inserted and the LED is on.</p> <p>Use the Device Manager to check for possible hardware conflicts. Click Start, Settings, Control Panel, System, Hardware and Device Manager. Verify the status of the ZyXEL M-202 under Network Adapter. (Steps may vary depending on the version of Windows).</p> <p>Install the ZyXEL M-202 in another computer.</p> <p>If the error persists, you may have a hardware problem. In this case, you should contact your local vendor.</p>
The ZyXEL Utility icon does not display.	<p>If you install the Funk Odyssey Client software on the computer, uninstall (remove) both the Funk Odyssey Client software and ZyXEL utility, and then install the ZyXEL utility again after restarting the computer.</p>

5.2 Problem with the Link Status

Table 20 Troubleshooting Link Quality

PROBLEM	CORRECTIVE ACTION
The link quality and/or signal strength is poor all the time.	<p>Search and connect to another AP with a better link quality using the Site Survey screen.</p> <p>Move your computer closer to the AP or the peer computer(s) within the transmission range.</p> <p>There may be too much radio interference (for example microwave or another AP using the same channel) around your wireless network. Relocate or reduce the radio interference.</p>

5.3 Problems Communicating With Other Computers

Table 21 Troubleshooting Communication Problem

PROBLEM	CORRECTIVE ACTION
In wireless station mode, the computer with the ZyXEL M-202 installed cannot communicate with the other computer(s).	<p>In Infrastructure Mode</p> <ul style="list-style-type: none">• Make sure that the AP and the associated computers are turned on and working properly.• Make sure the ZyXEL M-202 computer and the associated AP use the same SSID.• Change the AP and the associated wireless clients to use another radio channel if interference is high.• Make sure that the computer and the AP share the same security option and key. Verify the settings in the Profile Security Setting screen. <p>In Ad-Hoc (IBSS) Mode</p> <ul style="list-style-type: none">• Verify that the peer computer(s) is turned on.• Make sure the ZyXEL M-202 computer and the peer computer(s) are using the same SSID and channel.• Make sure that the computer and the peer computer(s) share the same security settings.• Change the wireless clients to use another radio channel if interference is high.

APPENDIX A

Product Specifications

Table 22 Product Specifications

PHYSICAL AND ENVIRONMENTAL	
Product Name	ZyXEL M-202 XtremeMIMO 802.11g Wireless USB 2.0 Adapter
Interface	USB 2.0 bus-powered
Standards	IEEE 802.11b IEEE 802.11g
Network Architectures	Infrastructure Ad-Hoc
Security	64/128/256-bit WEP, WPA, WPA2 Encryption
Operating Temperature	
Storage Temperature	
Operating Humidity	
Storage Humidity	
Power Consumption	
Voltage	
Weight	
Dimension	
RADIO SPECIFICATIONS	
Media Access Protocol	IEEE 802.11
Frequency	USA (FCC) & Canada 11 Channels: 2.4GHz~2.462GHz
Data Rate	11g: Orthogonal Frequency Division Multiplexing (OFDM): 54, 48, 36, 24, 18, 12, 9, 6 Mbps 11b: 11, 5.5, 2, 1 Mbps
Modulation	11g: OFDM (64QAM, 16QAM, QPSK, BPSK) 11b: PBCC, Direct Sequence Spread Spectrum (DSSS), (CCK, DQPSK, DBPSK)
Output Power	11g: 16dBm @ 54Mbps, 16dBm @ 48Mbps, 17dBm @ 36Mbps, 18dBm @ 24~6Mbps 11b: 18dBm @ 11Mbps
RX Sensitivity	11g (OFDM): -74dBm @ 54Mbps, -75dBm @ 48Mbps, -78dBm @ 36Mbps, -80dBm @ 24Mbps, -84dBm @ 18Mbps, -86dBm @ 12Mbps, -88dBm @ 9Mbps, -89dBm @ 6Mbps (typical) 11b (CCK): 11 Mbps: < -84 dBm (typical)
SOFTWARE SPECIFICATIONS	
Device Drivers	Microsoft Windows 2000, Windows XP
Roaming	IEEE 802.11b/g compliant

Table 22 Product Specifications (continued)

WPA	Wireless Protected Access, WPA2
WEP	64/128/256-bit WEP encryption

APPENDIX B

Disable Windows XP Wireless LAN Configuration Tool

Windows XP includes a configuration tool (also known as Wireless Zero Configuration (WZC)) for wireless devices.


Follow the steps below to disable the configuration tool in Windows XP after you install the ZyXEL Utility. The screen varies depending on the version of Windows XP service pack.

Via the Wireless Network System Tray Icon


If the network icon for wireless connections is not present in the system tray, see the next section.

- 1 Double-click the network icon for wireless connections in the system tray.


Figure 31 Windows XP: System Tray Icon




- 2 Windows XP SP1: When a **Wireless Network Connection** window displays, click **Advanced...**

Figure 32 Windows XP SP1: Wireless Network Connection

Windows XP SP2: When a **Wireless Network Connection** window displays, click **Change advanced settings** under **Related Tasks** and then the **Wireless Networks** tab.

Figure 33 Windows XP SP2: Wireless Network Connection

- 3 In the **Wireless Network Connection Properties** window, make sure the **Use Windows to configure my wireless network settings** check box is not selected. Click **OK**.

Figure 34 Windows XP SP1: Wireless Network Connection Properties**Figure 35** Windows XP SP2: Wireless Network Connection Properties

Via the Control Panel

- 1 If the icon for the wireless network connection is not in the system tray, click **Start**, **Control Panel** and double-click **Network Connections**.
- 2 Double-click on the icon for wireless network connection to display a status window as shown below.
- 3 Click **Properties** and click the **Wireless Networks** tab.

Figure 36 Windows XP SP1: Wireless Network Connection Status




Figure 37 Windows XP SP2: Wireless Network Connection Status




- 4 In the **Wireless Network Connection Properties** window, make sure the **Use Windows to configure my wireless network settings** check box is not selected. Click **OK**.

Figure 38 Windows XP SP1: Wireless Network Connection Properties



Figure 39 Windows XP SP2: Wireless Network Connection Properties




APPENDIX C

Management with Wireless Zero Configuration

This appendix shows you how to manage your ZyXEL wireless LAN adapter using the Windows XP wireless zero configuration tool.

Be sure you have the Windows XP service pack 2 installed on your computer. Otherwise, you should at least have the Windows XP service pack 1 already on your computer and download the support patch for WPA from the Microsoft web site.


Windows XP SP2 screen shots are shown unless otherwise specified. Click the help icon () in most screens, move the cursor to the item that you want the information about and click to view the help.

Activating Wireless Zero Configuration

Make sure the **Use Windows to configure my wireless network settings** check box is selected in the **Wireless Network Connection Properties** screen. Refer to [Appendix B on page 57](#).

If you see the following screen, refer to article 871122 on the Microsoft web site for information on starting WZC.

Figure 40 Windows XP SP2: WZC Not Available



Connecting to a Wireless Network

- 1 Double-click the network icon for wireless connections in the system tray to open the Wireless Network Connection Status screen.

Figure 41 Windows XP SP2: System Tray Icon




The type of the wireless network icon in Windows XP SP2 indicates the status of the ZyXEL wireless LAN adapter. Refer to the following table for details.

Table 23 Windows XP SP2: System Tray Icon

ICON	DESCRIPTION
	The ZyXEL wireless LAN adapter is connected to a wireless network.
	The ZyXEL wireless LAN adapter is in the process of connecting to a wireless network.
	The connection to a wireless network is limited because the network did not assign a network address to the computer.
	The ZyXEL wireless LAN adapter is not connected to a wireless network.


- 2 Windows XP SP2: In the **Wireless Network Connection Status** screen, click **View Wireless Networks** to open the **Wireless Network Connection** screen.

Figure 42 Windows XP SP2: Wireless Network Connection Status




Windows XP SP1: In the **Wireless Network Connection Status** screen, click **Properties** and the **Wireless Networks** tab to open the **Wireless Network Connection Properties** screen.

Figure 43 Windows XP SP1: Wireless Network Connection Status






- 3 Windows XP SP2: Click **Refresh network list** to reload and search for available wireless devices within transmission range. Select a wireless network in the list and click **Connect** to join the selected wireless network.

Figure 44 Windows XP SP2: Wireless Network Connection




The following table describes the icons in the wireless network list.

Table 24 Windows XP SP2: Wireless Network Connection

ICON	DESCRIPTION
	This denotes that wireless security is activated for the wireless network.
	This denotes that this wireless network is your preferred network. Ordering your preferred networks is important because the ZyXEL wireless LAN adapter tries to associate to the preferred network first in the order that you specify. Refer to the section on ordering the preferred networks for detailed information.
	This denotes the signal strength of the wireless network. Move your cursor to the icon to see details on the signal strength.

Windows XP SP1: Click **Refresh** to reload and search for available wireless devices within transmission range. Select a wireless network in the **Available networks** list, click **Configure** and set the related fields to the same security settings as the associated AP to add the selected network into the **Preferred** networks table. Click **OK** to join the selected wireless network. Refer to the section on security settings (discussed later) for more information.

Figure 45 Windows XP SP1: Wireless Network Connection Properties



4. Windows XP SP2: If the wireless security is activated for the selected wireless network, the **Wireless Network Connection** screen displays. You must set the related fields in the **Wireless Network Connection** screen to the same security settings as the associated AP and click **Connect**. Refer to the section about security settings for more information. Otherwise click **Cancel** and connect to another wireless network without data encryption.

If there is no security activated for the selected wireless network, a warning screen appears. Click **Connect Anyway** if wireless security is not your concern.

Figure 47 Windows XP SP2: Wireless Network Connection: WEP or WPA-PSK








Figure 48 Windows XP SP2: Wireless Network Connection: No Security



- 5 Verify that you have successfully connected to the selected network and check the connection status in the wireless network list or the connection icon in the **Preferred networks** or **Available networks** list.

The following table describes the connection icons.

Table 25 Windows XP: Wireless Networks

ICON	DESCRIPTION
	This denotes the wireless network is an available wireless network.
	This denotes the ZyXEL wireless LAN adapter is associated to the wireless network.
	This denotes the wireless network is not available.


Security Settings

When you configure the ZyXEL wireless LAN adapter to connect to a secure network but the security settings are not yet enabled on the ZyXEL wireless LAN adapter, you will see different screens according to the authentication and encryption methods used by the selected network.

Association

Select a network in the Preferred networks list and click Properties to view or configure security.

Figure 46 Windows XP: Wireless (network) properties: Association



The following table describes the labels in this screen.

Table 26 Windows XP: Wireless (network) properties: Association


LABEL	DESCRIPTION
Network name (SSID)	This field displays the SSID (Service Set Identifier) of each wireless network.
Network Authentication	This field automatically shows the authentication method (Share , Open , WPA or WPA-PSK) used by the selected network.
Data Encryption	This field automatically shows the encryption type (TKIP , WEP or Disable) used by the selected network.
Network Key	Enter the pre-shared key or WEP key. The values for the keys must be set up exactly the same on all wireless devices in the same wireless LAN.
Confirm network key	Enter the key again for confirmation.
Key index (advanced)	Select a default WEP key to use for data encryption. This field is available only when the network use WEP encryption method and the The key is provided for me automatically check box is not selected.
The key is provided for me automatically	If this check box is selected, the wireless AP assigns the ZyXEL wireless LAN adapter a key.

Table 26 Windows XP: Wireless (network) properties: Association (continued)

LABEL	DESCRIPTION
This is a computer-to-computer (ad hoc) network; wireless access points are not used	If this check box is selected, you are connecting to another computer directly.
OK	Click OK to save your changes.
Cancel	Click Cancel to leave this screen without saving any changes you may have made.

Authentication

Click the **Authentication** tab in the **Wireless (network) properties** screen to display the screen shown next. The fields on this screen are grayed out when the network is in Ad-Hoc mode or data encryption is disabled.

Figure 49 Windows XP: Wireless (network) properties: Authentication

The following table describes the labels in this screen.

Table 27 Windows XP: Wireless (network) properties: Authentication

LABEL	DESCRIPTION
Enable IEEE 802.1x authentication for this network	This field displays whether the IEEE 802.1x authentication is active. If the network authentication is set to Open in the previous screen, you can choose to disable or enable this feature.
EAP Type	Select the type of EAP authentication. Options are Protected EAP (PEAP) and Smart Card or other Certificate .
Properties	Click this button to open the properties screen and configure certificates. The screen varies depending on what you select in the EAP type field.


Table 27 Windows XP: Wireless (network) properties: Authentication (continued)

LABEL	DESCRIPTION
Authenticate as computer when computer information is available	Select this check box to have the computer send its information to the network for authentication when a user is not logged on.
Authenticate as guest when user or computer information is unavailable	Select this check box to have the computer access to the network as a guest when a user is not logged on or computer information is not available.
OK	Click OK to save your changes.
Cancel	Click Cancel to leave this screen without saving any changes you may have made.

Authentication Properties

Select an EAP authentication type in the **Wireless (network) properties: Authentication** screen and click the **Properties** button to display the following screen.

Protected EAP Properties

Figure 50 Windows XP: Protected EAP Properties


The following table describes the labels in this screen.

Table 28 Windows XP: Protected EAP Properties

LABEL	DESCRIPTION
Validate server certificate	Select the check box to verify the certificate of the authentication server.
Connect to these servers	Select the check box and specify a domain in the field below to have your computer connect to a server which resides only within this domain.
Trusted Root Certification Authorities:	Select a trusted certification authority from the list below. Note: You must first have a wired connection to a network and obtain the certificate(s) from a certificate authority (CA). Consult your network administrator for more information.
Do not prompt user to authorize new server or trusted certification authorities.	Select this check box to verify a new authentication server or trusted CA without prompting. This field is available only if you installed the Windows XP server pack 2.
Select Authentication Method:	Select an authentication method from the drop-down list box and click Configure to do settings.
Enable Fast Reconnect	Select the check box to automatically reconnect to the network (without re-authentication) if the wireless connection goes down.
OK	Click OK to save your changes.
Cancel	Click Cancel to leave this screen without saving any changes you may have made.

Smart Card or other Certificate Properties

Figure 51 Windows XP: Smart Card or other Certificate Properties



The following table describes the labels in this screen.

Table 29 Windows XP: Smart Card or other Certificate Properties

LABEL	DESCRIPTION
Use my smart card	Select this check box to use the smart card for authentication.
Use a certificate on this computer	Select this check box to use a certificate on your computer for authentication.
Validate server certificate	Select the check box to check the certificate of the authentication server.
Connect to these servers	Select the check box and specify a domain in the field below to have your computer connect to a server which resides only within this domain.
Trusted Root Certification Authorities:	Select a trusted certification authority from the list below. Note: You must first have a wired connection to a network and obtain the certificate(s) from a certificate authority (CA). Consult your network administrator for more information.
View Certificate	Click this button if you want to verify the selected certificate.
Use a different user name for the connection:	Select the check box to use a different user name when the user name in the smart card or certificate is not the same as the user name in the domain that you are logged on to.
OK	Click OK to save your changes.
Cancel	Click Cancel to leave this screen without saving any changes you may have made.

Ordering the Preferred Networks

Follow the steps below to manage your preferred networks.

- 1 Windows XP SP2: Click **Change the order of preferred networks** in the **Wireless Network Connection** screen. The screen displays as shown.






Figure 52 Windows XP SP2: Wireless Networks: Preferred Networks



Windows XP SP1: In the **Wireless Network Connection Status** screen, click **Properties** and the **Wireless Networks** tab to open the screen as shown.

Figure 53 Windows XP SP1: Wireless Networks: Preferred Networks

- 2 Whenever the ZyXEL wireless LAN adapter tries to connect to a new network, the new network is added in the **Preferred networks** table automatically. Select a network and click **Move up** or **Move down** to change it's order, click **Remove** to delete it or click **Properties** to view the security, authentication or connection information of the selected network. Click **Add** to add a preferred network into the list manually.

APPENDIX D

Types of EAP Authentication

This appendix discusses some popular authentication types: EAP-MD5, EAP-TLS, EAP-TTLS, PEAP and LEAP.

The type of authentication you use depends on the RADIUS server or the AP. Consult your network administrator for more information. Your wireless LAN device may not support all authentication types.

EAP-MD5 (Message-Digest Algorithm 5)

MD5 authentication is the simplest one-way authentication method. The authentication server sends a challenge to the wireless station. The wireless station 'proves' that it knows the password by encrypting the password with the challenge and sends back the information. Password is not sent in plain text.

However, MD5 authentication has some weaknesses. Since the authentication server needs to get the plaintext passwords, the passwords must be stored. Thus someone other than the authentication server may access the password file. In addition, it is possible to impersonate an authentication server as MD5 authentication method does not perform mutual authentication. Finally, MD5 authentication method does not support data encryption with dynamic session key. You must configure WEP encryption keys for data encryption.

EAP-TLS (Transport Layer Security)

With EAP-TLS, digital certifications are needed by both the server and the wireless stations for mutual authentication. The server presents a certificate to the client. After validating the identity of the server, the client sends a different certificate to the server. The exchange of certificates is done in the open before a secured tunnel is created. This makes user identity vulnerable to passive attacks. A digital certificate is an electronic ID card that authenticates the sender's identity. However, to implement EAP-TLS, you need a Certificate Authority (CA) to handle certificates, which imposes a management overhead.

EAP-TTLS (Tunneled Transport Layer Service)

EAP-TTLS is an extension of the EAP-TLS authentication that uses certificates for only the server-side authentications to establish a secure connection. Client authentication is then done by sending username and password through the secure connection, thus client identity is protected. For client authentication, EAP-TTLS supports EAP methods and legacy authentication methods such as PAP, CHAP, MS-CHAP and MS-CHAP v2.

PEAP (Protected EAP)

Like EAP-TTLS, server-side certificate authentication is used to establish a secure connection, then use simple username and password methods through the secured connection to authenticate the clients, thus hiding client identity. However, PEAP only supports EAP methods, such as EAP-MD5, EAP-MSCHAPv2 and EAP-GTC (EAP-Generic Token Card), for client authentication. EAP-GTC is implemented only by Cisco.

LEAP

LEAP (Lightweight Extensible Authentication Protocol) is a Cisco implementation of IEEE 802.1x.

Dynamic WEP Key Exchange

The AP maps a unique key that is generated with the RADIUS server. This key expires when the wireless connection times out, disconnects or reauthentication times out. A new WEP key is generated each time reauthentication is performed.

If this feature is enabled, it is not necessary to configure a default encryption key in the Wireless screen. You may still configure and store keys here, but they will not be used while Dynamic WEP is enabled.

Note: EAP-MD5 cannot be used with Dynamic WEP Key Exchange

For added security, certificate-based authentications (EAP-TLS, EAP-TTLS and PEAP) use dynamic keys for data encryption. They are often deployed in corporate environments, but for public deployment, a simple user name and password pair is more practical. The following table is a comparison of the features of authentication types.

Table 30 Comparison of EAP Authentication Types

	EAP-MD5	EAP-TLS	EAP-TTLS	PEAP	LEAP
Mutual Authentication	No	Yes	Yes	Yes	Yes
Certificate – Client	No	Yes	Optional	Optional	No
Certificate – Server	No	Yes	Yes	Yes	No
Dynamic Key Exchange	No	Yes	Yes	Yes	Yes
Credential Integrity	None	Strong	Strong	Strong	Moderate
Deployment Difficulty	Easy	Hard	Moderate	Moderate	Moderate
Client Identity Protection	No	No	Yes	Yes	No

WPA(2)

User Authentication

WPA or WPA2 applies IEEE 802.1x and Extensible Authentication Protocol (EAP) to authenticate wireless stations using an external RADIUS database.

Encryption

Both WPA and WPA2 improve data encryption by using Temporal Key Integrity Protocol (TKIP), Message Integrity Check (MIC) and IEEE 802.1x. In addition to TKIP, WPA2 also uses Advanced Encryption Standard (AES) in the Counter mode with Cipher block chaining Message authentication code Protocol (CCMP) to offer stronger encryption.

TKIP uses 128-bit keys that are dynamically generated and distributed by the authentication server. It includes a per-packet key mixing function, a Message Integrity Check (MIC) named Michael, an extended initialization vector (IV) with sequencing rules, and a re-keying mechanism.

TKIP regularly changes and rotates the encryption keys so that the same encryption key is never used twice.

The RADIUS server distributes a Pairwise Master Key (PMK) key to the AP that then sets up a key hierarchy and management system, using the PMK to dynamically generate unique data encryption keys to encrypt every data packet that is wirelessly communicated between the AP and the wireless stations. This all happens in the background automatically.

WPA2 AES (Advanced Encryption Standard) is a block cipher that uses a 256-bit mathematical algorithm called Rijndael.

The Message Integrity Check (MIC) is designed to prevent an attacker from capturing data packets, altering them and resending them. The MIC provides a strong mathematical function in which the receiver and the transmitter each compute and then compare the MIC. If they do not match, it is assumed that the data has been tampered with and the packet is dropped.

By generating unique data encryption keys for every data packet and by creating an integrity checking mechanism (MIC), TKIP makes it much more difficult to decrypt data on a Wi-Fi network than WEP, making it difficult for an intruder to break into the network.

The encryption mechanisms used for WPA(2) and WPA(2)-PSK are the same. The only difference between the two is that WPA(2)-PSK uses a simple common password, instead of user-specific credentials. The common-password approach makes WPA(2)-PSK susceptible to brute-force password-guessing attacks but it's still an improvement over WEP as it employs an easier-to-use, consistent, single, alphanumeric password.

Security Parameters Summary

Refer to this table to see what other security parameters you should configure for each Authentication Method/ key management protocol type. MAC address filters are not dependent on how you configure these security features.

Table 31 Wireless Security Relational Matrix

AUTHENTICATION METHOD/ KEY MANAGEMENT PROTOCOL	ENCRYPTION METHOD	ENTER MANUAL KEY	IEEE 802.1X
Open	None	No	Disable
			Enable without Dynamic WEP Key
Open	WEP	No	Enable with Dynamic WEP Key
		Yes	Enable without Dynamic WEP Key
		Yes	Disable
Shared	WEP	No	Enable with Dynamic WEP Key
		Yes	Enable without Dynamic WEP Key
		Yes	Disable
WPA	TKIP	No	Enable
WPA-PSK	TKIP	Yes	Enable
WPA2	AES	No	Enable
WPA2-PSK	AES	Yes	Enable

Index

Numerics

802.1x [41](#)

A

About [51](#)
about your ZyXEL M-202 [19](#)
Access Point Mode [24](#)
activating a profile [48](#)
Adapter [48](#)
Ad-Hoc [20,46](#)
Advanced Encryption Standard [77](#)
AES [77](#)
antenna [19](#)
antenna power output [55](#)
authentication [39, 69](#)
authentication method
 open system [29](#)
 shared key [31](#)

C

Certificate Authority [69](#)
channel [29](#)
configuration method
 important note [21](#)
 Odyssey Client Manager [21](#)
 Wireless Zero Configuration (WZC) [21](#)
 ZyXEL Utility [21](#)
connecting to a WLAN [38](#)
Copyright [3](#)
creating a new profile [45](#)
current configuration [35](#)
current connection status [35](#)
Customer Support [7](#)

D

data encryption [37](#)
Denmark, Contact Information [7](#)
driver version [51](#)
Dynamic WEP Key Exchange [76](#)

E

EAP [28, 75](#)
Encryption [27, 77](#)
Extensible Authentication Protocol [28](#)

F

FCC [4](#)
Finland, Contact Information [7](#)
France, Contact Information [7](#)

G

Germany, Contact Information [7](#)
getting started [19](#)
graphics icons key [18](#)

H

hardware connections [21](#)

I

initialization vector (IV) [77](#)
installation
 utility [19](#)

L

link information [35](#)

M

Message Integrity Check [27](#)

Message Integrity Check (MIC) [77](#)

MIC [27](#)

N

network type [35](#)

North America Contact Information [7](#)

Norway, Contact Information [7](#)

O

Odyssey Client Manager [21](#)

open system authentication [29](#)

P

Pairwise Master Key (PMK) [77](#)

passphrase [26](#), [39](#)

password phrase [26](#)

Power Saving Mode [49](#)

preamble [49](#)

product specifications [55](#)

profile [35](#), [44](#)

activation [48](#)

add new [44](#), [45](#)

delete [44](#)

edit [44](#)

information [44](#)

Q

Quick Start Guide [17](#), [21](#)

R

radio interference [53](#)

real-time data traffic statistics [36](#)

Regular Mail [7](#)

Related Documentation [17](#)

S

save power [49](#)

Scan Info [46](#)

security [26](#), [55](#)

data encryption [26](#)

Security Parameters [78](#)

Service [6](#)

Setup Key [30](#)

shared key authentication [29](#)

signal strength [37](#)

site survey [37](#)

connecting to a WLAN network [38](#)

scan [37](#)

security settings [38](#)

sleep mode [49](#)

Spain, Contact Information [8](#)

SSID [35](#), [37](#)

SSID (Service Set Identity) [25](#)

statistics [36](#)

support CD [17](#)

Support E-mail [7](#)

Sweden, Contact Information [8](#)

syntax conventions [17](#)

T

Telephone [7](#)

Temporal Key Integrity Protocol [27](#)

Temporal Key Integrity Protocol (TKIP) [77](#)

TKIP [27](#)

transmission rate [36](#), [45](#), [49](#)

transmission rate (Tx Rate) [25](#)

transmit key [39](#)

Trend Chart [36](#)

troubleshooting [53](#)

link status [53](#)

network communication [54](#)

starting ZyXEL Utility [53](#)

U

uninstalling ZyXEL Utility [51](#)
upgrading ZyXEL Utility [52](#)
 important step [52](#)
User Authentication [28, 77](#)

accessing [21](#)
help [22](#)
opening [22](#)
system tray icon [21](#)
upgrade [52](#)
version [51](#)

V

voltage [55](#)

W

Web Site [7](#)
WEP [26, 38, 39](#)
 manual setup [26, 39](#)
 passphrase [26, 39](#)
WEP (Wired Equivalent Privacy) [26](#)
Wi-Fi Protected Access [27](#)
Windows XP [21](#)
wireless LAN
 authentication [29](#)
 channel [25](#)
 introduction [25](#)
 security [26](#)
 SSID [25](#)
 transmission rate [25](#)
Wireless LAN (WLAN) [25](#)
wireless standard [55](#)
wireless station mode
 configuration [35](#)
WLAN
 Security parameters [78](#)
Worldwide Contact Information [7](#)
WPA [27, 39](#)
WPA2 [27, 39](#)
WPA2-Pre-Shared Key [27](#)
WPA2-PSK [27, 40](#)
WPA-PSK [27, 40](#)
WZC (Wireless Zero Configuration) [21](#)

Z

ZyXEL Limited Warranty
 Note [6](#)
ZyXEL Utility [21](#)